



T2 2:1 Transfer Pump

Proven Pumping Technology for Reliability and Durability



Designed for more output and better performance

- New quick-disconnect feature allows easier drum removal and faster change-out
- New design doubles the output – from 2.5 gpm to 5.0 gpm – helps get the job done faster
- Improved fluid intake easily handles higher viscosity materials – even in cold conditions
- Improved seal design for better performance and less maintenance downtime

PROVEN QUALITY. LEADING TECHNOLOGY.



Rely on the Graco T2 pump for increased output and longer life

Ordering Information

Graco T2 2:1 Transfer Pump

- 295616 Graco T2 2:1 Transfer Pump
- 246081 Graco T2 2:1 Transfer Pump, air supply kit, 10 ft x 3/4 in (3 m x 19 mm) supply hose and fittings
- 246898 Graco T2 2:1 Transfer Pump and 10 ft x 3/4 in (3 m x 19 mm) supply hose

Discover the advantages

- The new 2:1 air motor o-ring seal design is more durable and lasts longer – you spend more time spraying and less time on maintenance
- Lower pressure drop with higher viscosity materials at any ambient temperature
- Maintains performance in any environment – lower inlet pressure drop with higher viscosity materials in any ambient condition
- Provides consistent feed pressures and flow rates for consistent results
- Designed and manufactured by the worldwide leader in pump technology
- Reliable and cost-effective

Contact us today!
To receive product information or to request a hands-on demonstration, call 1-877-84GRACO or visit us online at www.graco.com.

Technical Specifications

Ratio	2.25:1
Maximum output – continuous	5.0 gpm (20 lpm)
Maximum output – intermittent	7.5 gpm (28 lpm)
Maximum input air pressure	180 psi (12.4 bar, 1.24 MPa)
Maximum output fluid pressure	405 psi (27.9 bar, 2.79 MPa)
Maximum ambient temperature	120°F (50°C)
Maximum fluid temperature	190°F (88°C)
Weight	21 lbs (9.5 kg)
Dimensions	54 in (137 cm) length; 3.5 in (8.9 cm) diameter (cap)
Operation and repair manual	311882

Longer lasting

Re-designed for long-lasting durability with less maintenance

Quick-release bung adapter

For easy drum removal without interference from hose connections

Corrosion-resistant components

Stainless steel wetted parts

PTFE seals

Improved performance for less maintenance



55 gallon drum not included.