

SDMO J40UC2 DIESEL GENERATOR SET

SDMO Diesel Generators powered by Mitsubishi, John Deere, Volvo Penta and MTU turbocharged diesel engines:

SDMO J40UC2 DIESEL GENERATOR SET

40Kw (50Kva) Standby, 36Kw (45Kva) Prime, 3 Phases, 0.8PF, 60Hz, 1800RPM, 208/120V

JOHN DEERE 3029TF270, Turbo-charged, heavy duty diesel engine, 4 stroke, 1800rpm, EPA compliant

MECC ALTE ECO32-3S, 12 lead brushless alternator. IP23 drip-proof protection, Insulation class H. Automatic voltage regulation.

MERLIN GERIN, Main line circuit breaker, 3 pole, output rated

SDMO NEXYS, Digital auto-start control panel. All alarms, genset parameters, control functions and indicators, CE and UL compliant

STANDARD FEATURES

- Open version
- Auto Start control feature included for interoperation with ATS/AMF
- Incorporated metallic fuel tank, High capacity: 100L
- EPA compliant engine as per the U.S. Environmental Protection Agency regulations
- Single bearing alternator IP23, Insulation class H/H, AVR SR7
- Radiator for wiring T° of 50°C [122°F] max with mechanical fan
- Microprocessor control panel
- 12V charging alternator and starter
- 12V charged DC starting battery with electrolyte and cables
- Industrial class silencer, muffler
- Dry type air filter, fuel filter and oil filter elements installed
- Mechanically welded chassis with vibration isolators
- User guide and Maintenance manual (English, French and Spanish)
- Each unit prototype and factory tested prior to shipping
- All other Standard features, please see catalog

Call for your Special Price on this unit -
LEAD TIME 2-3 WEEKS

We look forward to your order. Rheis Asbury 763 383 8386